

Connector Kits for Field Installation

Part #	Installed Connector Side View	Connector Kit Parts	Connector Kit Parts #	Diameter	Max Temp.	Compatible Cables
CC-A2A-175 CC-A2A-190 CC-A2A-250 CC-A2A-360		 2 Socket MIL-Style Connector Kit	CC-A2A-175 CC-A2A-190 CC-A2A-250 CC-A2A-360	.175" (4,5 mm) .190" (4,8 mm) .250" (6,4 mm) .360" (9,1 mm)	250°F (121°C) 250°F (121°C) 250°F (121°C) 250°F (121°C)	CB102, CB110 CB111 CB103 CB206
Supplied with epoxy and syringe (MH109-3A)						
CC-A2N		 2 Socket MIL-Style Connector Kit, High Temperature	CC-A2N	.310" (7,8 mm)	250°F (121°C)	CB102, CB103, CB110, CB111, CB206
Supplied with epoxy and syringe (MH109-3A)						
CC-A2R		 2 Socket MIL-Style Connector Kit, High Temperature	CC-A2R	.375" (9,5 mm)	392°F (200°C)	CB102, CB111
Supplied with epoxy and syringe (MH109-3A)						
CC-A2S		 2 Socket MIL-Style Connector Kit, Sulfuric Acid	CC-A2S	.375" (9,5 mm)	392°F (200°C)	CB102, CB111
Supplied with epoxy and syringe (MH109-3A)						
CC-A3A-175 CC-A3A-190 CC-A3A-250 CC-A3A-360		 3 Socket MIL-Style Connector Kit	CC-A3A-175 CC-A3A-190 CC-A3A-250 CC-A3A-360	.175" (4,5 mm) .190" (4,8 mm) .250" (6,4 mm) .360" (9,1 mm)	250°F (121°C) 250°F (121°C) 250°F (121°C) 250°F (121°C)	CB112 CB117 CB105, CB218 CB218
Supplied with epoxy and syringe (MH109-3A)						
CC-A3N		 3 Socket MIL-Style Connector Kit, High Temperature	CC-A3N	.310" (7,8 mm)	250°F (121°C)	CB105, CB112 CB218
Supplied with epoxy and syringe (MH109-3A)						
CC-A3R		 3 Socket MIL-Style Connector Kit	CC-A3R	.375" (9,5 mm)	392°F (200°C)	CB112, CB218
Supplied with epoxy and syringe (MH109-3A)						
CC-A3S		 3 Socket MIL-Style Connector Kit	CC-A3S	.375" (9,5 mm)	392°F (200°C)	CB112
Supplied with epoxy and syringe (MH109-3A)						
CC-B2A-175 CC-B2A-190 CC-B2A-250		 2 Socket Seal Tight Boot Connector Kit	CC-B2A-175 CC-B2A-190 CC-B2A-250	.175" (4,5 mm) .190" (4,8 mm) .250" (6,4 mm)	250°F (121°C) 250°F (121°C) 250°F (121°C)	CB102, CB110 CB111 CB103, CB206
Supplied with epoxy and syringe (MH109-3A)						
CC-B2R-175 CC-B2R-190 CC-B2R-250		 2 Socket Seal Tight Boot Connector Kit, High Temperature	CC-B2R-175 CC-B2R-190 CC-B2R-250	.175" (4,5 mm) .190" (4,8 mm) .250" (6,4 mm)	392°F (200°C) 392°F (200°C) 392°F (200°C)	CB102 CB111 CB206
Supplied with epoxy and syringe (MH109-3A)						
CC-B3A-175 CC-B3A-190 CC-B3A-250		 3 Socket Seal Tight Boot Connector Kit	CC-B3A-175 CC-B3A-190 CC-B3A-250	.175" (4,5 mm) .190" (4,8 mm) .250" (6,4 mm)	250°F (121°C) 250°F (121°C) 250°F (121°C)	CB112 CB105, CB117 CB105, CB218
Supplied with epoxy and syringe (MH109-3A)						
CC-B3R-175 CC-B3R-190 CC-B3R-250		 3 Socket Seal Tight Boot Connector Kit	CC-B3R-175 CC-B3R-190 CC-B3R-250	.175" (4,5 mm) .190" (4,8 mm) .250" (6,4 mm)	392°F (200°C) 392°F (200°C) 392°F (200°C)	CB112 CB119 CB212, CB218
Supplied with epoxy and syringe (MH109-3A)						

