



























# Cabling: 2 Conductor

Part No.	Jacket Material	Use	Conductor Qty.	Shielding Method	Max Temp.	Cable Diameter Weight/Ft.	Wire Gauge	Ratings/Certifications
<b>CB102</b>	Red Teflon®  	Permanent Monitoring	2 Conductor	Foil with Drain Wire	302°F (150°C)	.175 in (4,5 mm) 29.1 lbs./1000 ft.	AWG = 20	  RoHS PLENUM
<b>Compatible Connectors:</b> A2A, A2E, A2N, A2P, A2R, A2S, A2U, A2V, A2Y, B2A, B2N, B2R, D2H, D2J, E, EBLK, ERED, EMPP, EX, F, FBLK, FRED, FX, FX90, J2A, J2N, J2P, L, M2A, M2N, M2P, R2C, Z								
<b>CB103</b>	Black Polyurethane  	Permanent Monitoring/ Portable Measurement	2 Conductor	Braided Shield with Drain Wire	250°F (121°C)	.245 in (6 mm) 41.0 lbs./1000 ft.	AWG = 20	 RoHS
<b>Compatible Connectors:</b> A2A, A2E, A2N, A2P, A2R, A2S, A2U, A2V, A2Y, B2A, B2N, B2R, D2C, D2CG, D2D, D2H, E, EBLK, ERED, EMPP, EX, F, FBLK, FRED, FX, FX90, J2A, J2C, J2N, J2P, K2C, L, R2C, R2J, Z								
<b>CB104</b>	Black Polyurethane, Coiled  	Portable/ Permanent Measurement	2 Conductor	Braided Shield	250°F (121°C)	.210 in (5,3 mm) 0.45 lbs./10 ft.	AWG = 22	RoHS 
<b>Compatible Connectors:</b> A2U, D2C, D2CG, D2D, D2H, E, EX, F, FX, FX90, J2C, K2C, L, R2C, Z								
<b>CB108</b>	Black Polyurethane, Light Weight, Coiled  	Portable Measurement	2 Conductor	Braided Shield	250°F (121°C)	.170 in (4 mm) 0.30 lbs./10 ft.	AWG = 24	RoHS 
<b>Compatible Connectors:</b> A2U, D2C, D2CG, D2D, D2H, E, EX, F, FX, FX90, J2C, K2C, L, R2C, Z								
<b>CB110</b>	Black Polyurethane, Light Weight  	Permanent Monitoring/ Portable Measurement	2 Conductor	Braided Shield with Drain Wire	250°F (121°C)	.175 in (4,5 mm) 26.9 lbs./1000 ft.	AWG = 20	 RoHS
<b>Compatible Connectors:</b> A2A, A2E, A2N, A2P, A2R, A2S, A2U, A2V, A2Y, B2A, B2N, B2R, D2C, D2CG, D2D, D2H, E, EBLK, ERED, EMPP, EX, F, FBLK, FRED, FX, FX90, J2A, J2C, J2N, J2P, K2C, L, R2C, R2J, Z								
<b>CB111</b>	Yellow Teflon®  	Permanent Monitoring	2 Conductor	Braided Shield with Drain Wire	302°F (150°C)	.190 in (4,8 mm) 33.5 lbs./1000 ft.	AWG = 20	  RoHS PLENUM
<b>Compatible Connectors:</b> A2A, A2E, A2N, A2P, A2R, A2S, A2U, A2V, A2Y, B2A, B2N, B2R, D2C, D2CG, D2H, D2J, E, EBLK, ERED, EMPP, EX, F, FBLK, FRED, FX, FX90, J2A, J2C, J2P, K2C L, R2C, V2N, V2R, Z								
<b>CB124</b>	Brown, Low Smoke Zero Halogen, Polyurethane  	Permanent Monitoring	2 Conductor	Braided Shield with Drain Wire	250°F (121°C)	.250 in (6,4 mm) 41.0 lbs./1000 ft.	AWG = 20	RoHS  LSZH
<b>Compatible Connectors:</b> A2A, E, F, L, Z								
<b>CB193</b>	Blue Polyurethane  	Permanent Monitoring/ Portable Measurement	2 Conductor	Braided Shield with Drain Wire	250°F (121°C)	.245 in (6 mm) 41.0 lbs./1000 ft.	AWG = 20	 RoHS
<b>Compatible Connectors:</b> A2A, A2E, A2N, A2P, A2R, A2S, A2U, A2V, A2Y, B2A, B2N, B2R, D2C, D2CG, D2D, D2H, E, EBLK, ERED, EMPP, EX, F, FBLK, FRED, FX, FX90, J2A, J2C, J2N, J2P, K2C, L, R2C, R2J, Z								

\* Teflon® is a registered trademark of DuPont.

Note: Bulk cable purchase discount is available for cable purchased in 1000 ft. reels

Backed by our Unconditional Lifetime Warranty

[www.ctconline.com](http://www.ctconline.com)

