m

FCTION

ហ

SSB1000



Product Features -

Enclosures With DIN Rail Mountable Modules for Multiple Inputs and a Switched Output

The modules feature BNC and 2 Pin connection options to suit your preferred data collector

- Provides a switched output from remotely installed sensors to a data collector through a BNC and a 2 Pin MIL spec connector
- Accepts input from: Sensors, Proximity probes Temperature probes
- Quick-release input terminal blocks




Steel DIN Rail **Clip for Secure** Attachment

Specifications


	SSB1000	SSB2000
Inputs	Terminal block 3 inputs per channel (+, -, shield)	
Switched Output	BNC jack and 2 Pin MIL	
Continuous Output	Multi-pin connector for interface with online systems (optional) Requires JB907-3A	
Rating	NEMA 4X (IP66)	
Door Closure	Snap Latch	Twist Lock
Material	Fiberglass	Stainless Steel
Temperature Rating	-58° to 180° F (-50° to 82° C)	

SSB2000





Ordering Information



Example Part Number: SSB1000-12C erglass single output switch box, 12 sensor capacity, cord grip entry

- No punch outs are provided in the enclosure for cable entry. User may install any fitting required.
- ** For use with rigid body conduit.
- †Stainless Steel enclosure only

Optional Accessories:

 T-Plug output connector for online systems interface. Note: End user is responsible for providing enclosure exit when using this option