

Power Amplifier (200W)

Model: YE5872A

Features:

- Indicator for voltage and current output
- Indicator for output signal
- Output current can be adjusted from 2A to 10A
- Hot protect for output transistor
- Indicator for output transistor invalidation



Specifications:

Input	
Input impedance	$\geq 10k\Omega$
Output	
Rated power output	200VArms
Rated voltage output	14Vrms
Rated current output	15Arms
Non-linearity distortion	<1%
Signal / Noise rate	Constant Voltage $\geq 70\text{dB}$; Constant Current $\geq 60\text{dB}$
Indicator meter Tolerance	$< \pm 8\%$
Environmental Characteristics	
Temperature	Operating: 0°C to 70°C ; Storage: -55°C to 85°C
Moisture	Maximum 90%R.H.
Frequency Characteristics	
Frequency Range (Hz)	DC input 0 to $15\text{kHz} \pm 0.5\text{dB}$; AC input 20 to $50\text{kHz} \pm 1\text{dB}$

SINOCERA PIEZOTRONICS, INC. 42 Wugang Rd, Yangzhou, Jiangsu, P.R.China 225007

Phone: +86 514 87322487, Fax: +86 514 8734 8670, E-mail: export@china-yec.com, Web: <http://en.china-yec.com/>

In the interest of constant product improvement, we reserve the right to change specifications without notice.

Power Amplifier (200W)

Model: YE5872A

	Full power 5-10kHz, half power 0-50kHz
PROTECT	
Current output limited	3-15Arms (modifiable)
Hot limit of transistor	$\leq 85^{\circ}\text{C} \pm 5^{\circ}\text{C}$
Physical characteristics	
Dimensions	400mm (W) X166mm (H)X320mm (D)
Weight	About 15Kg
Gain	
Constant voltage type	5V/V \pm 2dB (1kHz)
Constant current type	8A/V \pm 2dB (1kHz)
Power Supply	
Power source	AC220V(+5%~-10%)50Hz 3A
Accessories	
Input cable	One 2m double-BNC cable
Output cable	One 4-core cable
Power supply cable	One AC supply cable
Fuse	Four 5A(Φ 6mm X 30mm)

SINOCERA PIEZOTRONICS, INC. 42 Wugang Rd, Yangzhou, Jiangsu, P.R.China 225007

Phone: +86 514 87322487, Fax: +86 514 8734 8670, E-mail: export@china-yec.com, Web: <http://en.china-yec.com/>

In the interest of constant product improvement, we reserve the right to change specifications without notice.