

# LP384-M12E Series



**Loop Power Sensor, 4-20 mA Output Proportional to Vibration in Acceleration, Side Exit 4 Pin M12 Connector, M8x1.25 Captive Bolt**



## Product Features


### 4-20 mA Current Proportional to Vibration in Acceleration

- ▶ Peak and RMS Outputs Available
- ▶ Transmits Signals Over Long Distances with No Signal Loss
- ▶ Outputs to PLC, DCS, SCADA

**LP384-XXX-M12E**

4 Pin M12 Connector

| Connector Pin | Polarity              |
|---------------|-----------------------|
| 1             | (+) Loop Power        |
| 2             | (-) Loop Power Return |
| 3             | Not Used              |
| 4             | Not Used              |



## Built To Order

| Specifications              |  |  | Standard                |  |  | Metric               |  |  |
|-----------------------------|--|--|-------------------------|--|--|----------------------|--|--|
| Part Number                 |  |  | LP384-M12E              |  |  |                      |  |  |
| Tolerance: 4 mA             |  |  | (± 10%)                 |  |  |                      |  |  |
| Tolerance: 20 mA            |  |  | (± 10%)                 |  |  |                      |  |  |
| Electrical                  |  |  |                         |  |  |                      |  |  |
| Settling Time               |  |  | <60 Seconds             |  |  |                      |  |  |
| Voltage Source              |  |  | 15-30 VDC               |  |  |                      |  |  |
| Case Isolation              |  |  | >10 <sup>8</sup> ohm    |  |  |                      |  |  |
| Environmental               |  |  |                         |  |  |                      |  |  |
| Operating Temperature Range |  |  | -4 to 212 °F            |  |  | -20 to 100 °C        |  |  |
| Electromagnetic Sensitivity |  |  | CE                      |  |  |                      |  |  |
| Submersible Depth           |  |  | 200 ft.                 |  |  | 60 m                 |  |  |
| Specifications              |  |  | Standard                |  |  | Metric               |  |  |
| Physical                    |  |  |                         |  |  |                      |  |  |
| Sensing Element             |  |  | Welded, Hermetic        |  |  |                      |  |  |
| Sensing Structure           |  |  | Shear Mode              |  |  |                      |  |  |
| Weight                      |  |  | 4.9 oz                  |  |  | 140 grams            |  |  |
| Case Material               |  |  | 316L Stainless Steel    |  |  |                      |  |  |
| Mounting Thread             |  |  | M8x1.25 Captive Bolt    |  |  |                      |  |  |
| Connector (Non-Integral)    |  |  | 2 Pin MIL-C-5015        |  |  |                      |  |  |
| Mounting Torque             |  |  | 2 to 5 ft. lbs.         |  |  | 2,7 to 6,8 Nm        |  |  |
| Mounting Hardware Supplied  |  |  | 1/4-28 Captive Bolt     |  |  | M8x1.25 Captive Bolt |  |  |
| Calibration Certificate     |  |  | Current Output @ 100 Hz |  |  |                      |  |  |

## Ordering Information

|                                                                                   |                                                                                                                                      |                                                      |                                                                                                                                                                                                                                              |                                                                                                                                       |                                                                                                                                                                         |                                                                                                                                                                         |
|-----------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <div> <div></div> <div>/LP384 -</div> <div> <div></div> <div></div> </div> </div> |                                                                                                                                      | <div> <div></div> </div>                             | <div> <div></div> <div>-</div> <div> <div></div> <div></div> <div></div> <div></div> </div> </div>                                                                                                                                           |                                                                                                                                       | <div> <div></div> <div>/</div> <div> <div></div> <div></div> </div> </div>                                                                                              | <div> <div></div> <div>/</div> <div> <div></div> <div></div> </div> </div>                                                                                              |
| <b>Bolt Type</b><br><br><b>Blank</b> = M8x1.25                                    | <b>Measurement Range</b><br><br><b>0</b> = 0-1 g<br><b>2</b> = 0-2 g<br><b>5</b> = 0-5 g<br><b>10</b> = 0-10 g<br><b>20</b> = 0-20 g | <b>Type</b><br><br><b>P</b> = Peak<br><b>R</b> = RMS | <b>Frequency Range ±3dB</b><br><br><b>1</b> = 600-60000 CPM (10-1000 Hz)<br><b>2</b> = 180-150000 CPM (3-2500 Hz)<br><b>3</b> = 180-60000 CPM (3-1000 Hz)<br><b>4</b> = 180-300000 CPM (3-5000 Hz)<br><b>5</b> = 180-600000 CPM (3-10000 Hz) | <b>Style</b><br><br><b>1E</b> = 2 Pin MIL C-5015<br><b>2E</b> = Integral Cable<br><b>3E</b> = Armor Jacket<br><b>M12E</b> = 4 Pin M12 | <b>Armor Length (Integral)</b><br><br><b>010</b> = 10 ft/3 m<br><b>020</b> = 20 ft/6 m<br><b>030</b> = 30 ft/9 m<br><b>050</b> = 50 ft/15 m<br><b>100</b> = 100 ft/30 m | <b>Cable Length (Integral)</b><br><br><b>010</b> = 10 ft/3 m<br><b>020</b> = 20 ft/6 m<br><b>030</b> = 30 ft/9 m<br><b>050</b> = 50 ft/15 m<br><b>100</b> = 100 ft/30 m |
| <div>*Custom Lengths Available Upon Request</div>                                 |                                                                                                                                      |                                                      |                                                                                                                                                                                                                                              |                                                                                                                                       |                                                                                                                                                                         |                                                                                                                                                                         |