

MX702

Single Axis Mini-MAXX Box, Enclosed Individual BNC Connectors,
Polycarbonate Enclosure, NEMA 4X (IP66) Rated, Sensor Input Options: 1 to
4 Single Output Sensors




Product Features

Provides a low-cost solution that is ideal for harsh environments, including coastal areas exposed to salt air

Internally earth grounded for noise reduction

- ▶ 316L stainless steel latch and mounting feet
- ▶ Terminal strip located behind BNC panel for easy wiring with grounding



Specifications

Temperature Range	-58 °F (-50 °C) to 180 °F (82 °C)
Enclosure Material	Polycarbonate
Inputs	Conduit or Cord Grips
Outputs	BNC Jack per Channel, Electrically Isolated
Sensor Input Options	1, 2, 3, and 4 Channel Options
Rating	NEMA 4X
Door Closure	Flip Latch
Dimensions	5.05 x 4.19 x 2.82 in. (128.2 x 106.5 x 71.6 mm)
Cord Grips	Optional
Resistance	Resistant to Hose-Directed Fluid and Corrosion

Ordering Information

MX			-		
Enclosure Type		Sensor Inputs (Single Output)		Input Options	
502 = Aluminum Enclosure 702 = Fiberglass Enclosure		1 = 1 Sensors 2 = 2 Sensors 3 = 3 Sensors 4 = 4 Sensors		A = No Factory Penetrations* B = Conduit Fitting** C = Nylon Cord Grips N = Nickel Plated Brass Cord Grips† S = Stainless Steel Cord Grips†	
*No punch outs are provided in the enclosure for cable entry. User may install any fitting required. **For use with conduit. †Aluminum enclosures only					