

AC215 Series

Premium, Low Frequency Accelerometer, Side Exit 2 Pin Connector, 1,000 mV/g, $\pm 5\%$



Product Features

Designed for Low-Speed Rotors, Wind Turbine Main Bearings, Gear Box Inputs, and May Also Be Used for High Frequency Detection

May be Used with Any Application That Requires Low and High Frequency Measurements


- ▶ 1000 mV/g Sensitivity
- ▶ 0.1 Hz to 8 kHz Frequency Response ($\pm 3\text{dB}$)
- ▶ Standard 2 Pin MIL Connection or Integral Cable

Note: Integral Cable Options are Only for Permanent Monitoring Applications

-6N Integral Cable Option Features Food Safe FDA Compliant 21 CFR 177.1330 Polyolefin Heat Shrink

AC215-1D 2 Pin Connector


Connector Pin	Polarity
A	(+) Signal/Power
B	(-) Common



Stock Product

AC215-2D & -7A 2D = CB103 Integral Cable 7A = CB124 Integral Cable


Conductor	Polarity
Red	(+) Signal/Power
Black	(-) Common
Shield	Cable Drain Wire



Built To Order

AC215-3D CB206 Armored Integral Cable


Conductor	Polarity
Red	(+) Signal/Power
Black	(-) Common
Shield	Cable Drain Wire



Built To Order

AC215-6D CB611 Heavy Duty Armored Integral Cable


Conductor	Polarity
Red	(+) Signal/Power
Black	(-) Common
Shield	Cable Drain Wire



Built To Order

AC215-6N CB111 FEP Jacketed Integral Cable

Conductor	Polarity
Red	(+) Signal/Power
Black	(-) Common
Shield	Cable Drain Wire



Built To Order

Specifications	Standard	Metric	Specifications	Standard	Metric
Part Number	AC215	M/AC215	Environmental		
Sensitivity ($\pm 5\%$)	1000 mV/g		Operating Temperature Range	-58 to 250 °F	-50 to 121 °C
Frequency Response ($\pm 3\text{dB}$)	6-480,000 CPM	0.1-8000 Hz	Maximum Shock Protection	5000 g, peak	
Frequency Response ($\pm 10\%$)	36-180,000 CPM	0.6-3000 Hz	Electromagnetic Sensitivity	CE	
Dynamic Range	± 7 g, peak *Vsource $\geq 22\text{V}$, 12Vbias		Sealing	Welded, Hermetic	
Transverse Sensitivity	$\leq 5\%$		SIL Rating	SIL 2	
Electrical			Physical		
Settling Time	< 2 seconds		Sensing Element	PZT Ceramic	
Voltage Source	18-30 VDC		Sensing Structure	Shear Mode	
Constant Current Excitation	2-10 mA		Weight	5.7 oz	162 g
Spectral Noise @ 10 Hz	1.3 $\mu\text{g}/\sqrt{\text{Hz}}$		Case Material	316L Stainless Steel	
Spectral Noise @ 100 Hz	0.2 $\mu\text{g}/\sqrt{\text{Hz}}$		Connector (Non-Integral)	2 Pin MIL-C-5015	
Spectral Noise @ 1000 Hz	0.1 $\mu\text{g}/\sqrt{\text{Hz}}$		Resonant Frequency	1,020,000 CPM	18000 Hz
Output Impedance	< 100 ohm		Mounting Torque	2 to 5 ft. lbs.	2.7 to 6.8 Nm
Bias Output Voltage	10-14 VDC		Mounting Hardware Supplied	1/4-28 Captive Bolt	M6x1 Captive Bolt
Case Isolation	> 10^8 ohm		Calibration Certificate	CA10	

Typical Frequency Response

