

AC225 Series

Low Cost, Miniature Industrial High G and High Frequency Mini-MIL Accelerometer, Side Exit 2 Pin Mini-MIL Connector, 10 mV/g, ±15%



VIBRATION ANALYSIS HARDWARE



Product Features

Very High 500 g Side-Exit Accelerometer for High Amplitude Applications


Helps to Detect Gearbox Defects and Other High Frequency Faults

- ▶ 1,0-15000 Hz (60-900,000 CPM) Frequency Response
- ▶ 10 mV/g ±15% Sensitivity
- ▶ 32 kHz Resonant Frequency

AC225-1A

2 Pin Mini Mil Connector

Connector Pin	Polarity
A	(+) Signal/Power
B	(-) Common




Stock Product

AC225-2A

CB110 Integral Cable

Conductor	Polarity
Red	(+) Signal/Power
Black	(-) Common
Shield	Cable Drain Wire




Built To Order

AC225-3A

CB206 Armored Integral Cable

Conductor	Polarity
Red	(+) Signal/Power
Black	(-) Common
Shield	Cable Drain Wire




Built To Order

AC225-6A

CB611 Heavy Duty Armored Integral Cable

Conductor	Polarity
Red	(+) Signal/Power
Black	(-) Common
Shield	Cable Drain Wire




Built To Order

AC225-6N

CB111 Integral Cable

Conductor	Polarity
Red	(+) Signal/Power
Black	(-) Common
Shield	(-) Common



Built To Order

Specifications	Standard	Metric	Specifications	Standard	Metric
Part Number	AC225	M/AC225	<u>Environmental</u>		
Sensitivity (±15%)	10 mV/g		Operating Temperature Range	-58 to 250 °F	-50 to 121 °C
Frequency Response (±3dB)	60-900,000 CPM	1,0-15000 Hz	Maximum Shock Protection	5,000 g, peak	
Dynamic Range	± 500 g, peak *Vsource ≥ 22V, 12Vbias		Electromagnetic Sensitivity	CE	
Transverse Sensitivity	≤5%		Sealing	Welded, Hermetic	
<u>Electrical</u>			Submersible Depth	200 ft.	60 m
Settling Time	<2 seconds		SIL Rating	SIL 2	
Voltage Source	18-30 VDC		<u>Physical</u>		
Constant Current Excitation	2-10 mA		Sensing Element	PZT Ceramic	
Spectral Noise @ 10 Hz	100 µg/√Hz		Sensing Structure	Shear Mode	
Spectral Noise @ 100 Hz	19 µg/√Hz		Weight	2.1 oz	60 grams
Spectral Noise @ 1000 Hz	5 µg/√Hz		Case Material	316L Stainless Steel	
Output Impedance	<100 ohm		Connector (Non-Integral)	2 Pin mini-MIL	
Bias Output Voltage	10-14 VDC		Resonant Frequency	1,920,000 CPM	32000 Hz
Case Isolation	>10 ⁸ ohm		Mounting Torque	2 to 5 ft. lbs.	2,7 to 6,8 Nm
			Mounting Hardware Supplied	1/4-28 Captive Bolt	M6x1 Captive Bolt
			Calibration Certificate	CA10	

Typical Frequency Response

