

LP662-M12A Series

Premium Dual Output Loop Power Sensor, 4-20 mA Output Proportional to Vibration in Acceleration with °C Temperature Output, Top Exit 4 Pin M12 Connector



Product Features

New 2nd-Order Filters Deliver Sharper Response and Greater Stopband Attenuation for Cleaner Measurements


Enhanced Temperature Range of -40 to 257 °F (-40 to 125 °C), and Other Improved Specs Including:

- ▶ Capable of a 2 Hz Low Frequency Response
- ▶ New Measurement Ranges of 0 to 0.25 g & 0 to 0.5 g

LP662-XXX-M12A

4 Pin M12 Connector

Connector Pin	Polarity
1	(+) Loop Power
2	(-) Loop Power Return
3	Not Used
4	Not Used



Built To Order

Specifications	Standard	Metric	Specifications	Standard	Metric
Part Number	LP662-M12A	M/ or M8/LP662-M12A	Physical		
Temperature Output	10 mV/°C		Sensing Element	PZT Ceramic	
	within the range -40 to 85 °C		Sensing Structure	Shear Mode	
Tolerance: 4 mA	(± 10%)		Weight	2.0 oz	86 grams
Tolerance: 20 mA	(± 10%)		Case Material	316L Stainless Steel	
Tolerance: Temperature	(± 5 °C)		Mounting Thread	1/4-28 Blind Tapped Hole	
Electrical			Connector (Non-Integral)	4 Pin M12	
Settling Time	<30 Seconds		Mounting Torque	2 to 5 ft. lbs.	2.7 to 6.8 Nm
Voltage Source	15-30 VDC		Mounting Hardware Supplied	1/4-28 Stud	M6x1 or M8x1.25 Adapter Stud
Case Isolation	>10 ⁸ ohm		Calibration Certificate	Current Output @ 100 Hz	
Environmental					
Operating Temperature Range	-40 to 257 °F	-40 to 125 °C			
Electromagnetic Sensitivity	CE				
Sealing	Welded, Hermetic				
Submersible Depth	200 ft.	60 m			

Ordering Information

[] /LP662 - []		[]		[]		[]		[]		[]	
Stud Type Blank = 1/4-28 M = M6x1 M8 = M8x1.25	Measurement Range 0 = 0-0.25 g 1 = 0-0.5 g 2 = 0-1 g 3 = 0-2 g 4 = 0-5 g 5 = 0-10 g 6 = 0-20 g	Type P = Peak R = RMS	Frequency Range ±3dB 1 = 600-60000 CPM (10-1000 Hz) 2 = 120-150000 CPM (2-2500 Hz) 3 = 120-60000 CPM (2-1000 Hz) 4 = 120-300000 CPM (2-5000 Hz) 5 = 120-600000 CPM (2-10000 Hz)	Style 1A = 3 Pin MIL C-5015 2A = Integral Cable 3A = Armor Jacket M12A = 4 Pin M12	Integral Options		Armor Length (Integral) 010 = 10 ft/3 m 020 = 20 ft/6 m 030 = 30 ft/9 m 050 = 50 ft/15 m 100 = 100 ft/30 m		Cable Length (Integral) 010 = 10 ft/3 m 020 = 20 ft/6 m 030 = 30 ft/9 m 050 = 50 ft/15 m 100 = 100 ft/30 m		
*Custom Lengths Available Upon Request											