

TA218 Series

Dual Output Sensor, Temperature & Acceleration, Side Exit 3 Pin Connector,
50 mV/g, 10 mV/°C, ±10%



VIBRATION ANALYSIS HARDWARE



Product Features


High Performance in a Low-Cost Sensor

Helps to Detect Bearing Defects and Temperature Changes

- ▶ Temperature (10 mV/°C) and Acceleration (50 mV/g) Outputs in One Sensor via a Standard 3 Pin MIL Connection
- ▶ Popularly Sold with SC300 Series Signal Conditioners with Built-In Temperature Output

TA218-1A 3 Pin Connector


Connector	Polarity
Pin	
A	(+) Signal/Power
B	(-) Common
C	(+) Temperature Voltage



Stock Product

TA218-2A CB105 Integral Cable


Conductor	Polarity
Red	(+) Signal/Power
Black	(-) Common
White	(+) Temperature Voltage
Shield	Cable Drain Wire



Built To Order

TA218-3A CB218 Armored Integral Cable


Conductor	Polarity
Red	(+) Signal/Power
Black	(-) Common
White	(+) Temperature Voltage
Shield	Cable Drain Wire



Built To Order

TA218-6N CB119 FEP Jacketed Integral Cable

Conductor	Polarity
Red	(+) Signal/Power
Black	(-) Common
White	(+) Temperature Voltage
Shield	Cable Drain Wire



Built To Order

Specifications	Standard	Metric	Specifications	Standard	Metric
Part Number	TA218	M/TA218	Environmental		
Sensitivity (±10%)		50 mV/g	Operating Temperature Range	-40 to 250 °F	-40 to 121 °C
Frequency Response (±3dB)	60-600,000 CPM	1,0-10000 Hz	Maximum Shock Protection		5,000 g, peak
Frequency Response (±10%)	240-360,000 CPM	4,0-6000 Hz	Electromagnetic Sensitivity		CE
Dynamic Range		± 100 g, peak	Sealing		IP68
Temperature Measurement Range	-40 to 250°F	-40 to 121°C	Submersible Depth	200 ft	60 m
Temperature Output		10 mV/°C	SIL Rating		SIL 2
Temperature Sensor		750 mV = 25 °C (±1)	Physical		
Transverse Sensitivity		≤5%	Sensing Element		PZT Ceramic
Electrical			Sensing Structure		Shear Mode
Settling Time		5 seconds	Weight	5.6 oz	160 grams
Voltage Source		18-30 VDC	Case Material		316L Stainless Steel
Constant Current Excitation		2-10 mA	Connector (Non-Integral)		3 Pin MIL-C-5015
Spectral Noise @ 10 Hz		14 µg/√Hz	Resonant Frequency	1,260,000 CPM	21000 Hz
Spectral Noise @ 100 Hz		2.3 µg/√Hz	Mounting Torque	2 to 5 ft. lbs.	2,7 to 6,8 Nm
Spectral Noise @ 1000 Hz		2 µg/√Hz	Mounting Hardware Supplied	1/4-28 Captive Bolt	M6x1 Captive Bolt
Output Impedance		<100 ohm	Calibration Certificate		CA10
Bias Output Voltage		10-14 VDC			
Case Isolation		>10 ⁸ ohm			

Typical Frequency Response

